

Replacement Screws for Trigger

Replacement screw set for VC2TT.

Contains pre- and overtravel screws for all models. (5 pieces)



Spare part for Target Trigger for MKII, MKIII and MK IV

Attributes

- Name: Volquartsen Replacement Screws for Trigger
- Manufacturer: VOLQUARTSEN
- Product no.: BRD231481
- Mfr. No.: VC2TT-SP-0001
- Make: Volquartsen
- Delivery weight: 0.1kg

Table of Contents

- [Startpage](#)
- [Deutsch: Sicherheitshinweise für Volquartsen ErsatzSchrauben für Abzug](#)
- [English: Safety Instruction Guide for Volquartsen Replacement Screws for Trigger](#)

Sicherheitshinweise für Volquartsen ErsatzSchrauben für Abzug

Einführung

Herzlichen Glückwunsch zu Ihrem Kauf der Volquartsen ErsatzSchrauben für Abzug. Dieses Ersatzschraubenset ist speziell für die Modelle VC2TT, MKII, MKIII und MKIV konzipiert. Um die Sicherheit und ordnungsgemäße Verwendung des Produkts zu gewährleisten, lesen Sie bitte diese Sicherheitshinweise sorgfältig durch.

Allgemeine Sicherheitsrichtlinien

- Stellen Sie sicher, dass das Produkt für den vorgesehenen Gebrauch geeignet ist.
- Lagern Sie das Produkt an einem sicheren Ort, außerhalb der Reichweite von Kindern.
- Überprüfen Sie regelmäßig auf Anzeichen von Beschädigungen oder Abnutzung.
- Melden Sie unsichere Produkte oder Unfälle den zuständigen Behörden.
- Informieren Sie sich über Rückrufaktualisierungen auf der EU Safety GatePlattform.

Spezifische Sicherheitsvorkehrungen für die Verwendung

- Verwenden Sie nur die für Ihr Modell vorgesehenen Schrauben.
- Achten Sie darauf, dass alle Schrauben fest angezogen sind, um ein Lösen während des Gebrauchs zu verhindern.
- Verwenden Sie keine beschädigten Schrauben oder Teile.
- Tragen Sie bei der Installation geeignete Schutzausrüstung, wie z.B. Handschuhe und Schutzbrille.
- Halten Sie sich an die empfohlenen Anweisungen zur Installation und Verwendung.

Anweisungen zur Installation und Verwendung

1. Vorbereitung

- Stellen Sie sicher, dass Sie alle Teile des Ersatzschraubensets haben (5 Stück).
- Überprüfen Sie, ob Ihr Werkzeug für die Installation geeignet ist.

2. Installation

- Entfernen Sie die alten Schrauben vorsichtig mit dem geeigneten Werkzeug.
- Setzen Sie die neuen Vor und Nachlaufschrauben an den vorgesehenen Stellen ein.
- Ziehen Sie die Schrauben mit dem empfohlenen Drehmoment an, um sicherzustellen, dass sie fest sitzen.

3. Überprüfung

- Überprüfen Sie nach der Installation, ob alle Schrauben sicher angezogen sind.
- Testen Sie den Abzug, um sicherzustellen, dass er ordnungsgemäß funktioniert.

4. Verwendung

- Verwenden Sie das Produkt nur in Übereinstimmung mit den Anweisungen.
- Achten Sie darauf, dass Sie bei der Verwendung des Abzugs die Sicherheitsvorkehrungen einhalten.

Entsorgungsanweisungen

- Entsorgen Sie das Produkt gemäß den örtlichen Vorschriften für die Entsorgung von Elektronik und Metall.
- Stellen Sie sicher, dass alle Teile umweltgerecht recycelt werden, wo dies möglich ist.

Kontaktinformationen für weitere Unterstützung

Für Fragen oder Anliegen zu Ihrem Produkt wenden Sie sich bitte an den Hersteller oder an die Verkaufsstelle, bei der Sie das Produkt erworben haben.

Safety Instruction Guide for Volquartsen Replacement Screws for Trigger

Introduction

Thank you for choosing the Volquartsen Replacement Screws for Trigger. This guide provides important safety instructions and information to ensure the safe use of this product. Please read and follow these guidelines carefully to avoid any hazards and to ensure optimal performance.

General Safety Guidelines

- Always ensure that the firearm is unloaded before performing any maintenance or installation of parts.
- Store all components in a safe and secure location, out of reach of children and unauthorized users.
- Inspect the screws and the trigger assembly for any signs of damage before installation.
- Use only the specified replacement screws for the VC2TT model to maintain safety and functionality.
- Be aware of your surroundings when handling firearms and replacement parts.

Specific Safety Precautions for Use

- Ensure you are using the correct tools for installation to avoid damaging the screws or the trigger assembly.
- Avoid overtightening screws as this may lead to damage or malfunction of the trigger mechanism.
- If you are unsure about the installation process, seek assistance from a qualified gunsmith or firearms expert.
- Do not use the replacement screws if they are damaged or show signs of wear. Replace them immediately.
- Always follow the manufacturer's instructions for the trigger assembly to ensure safe operation.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is completely unloaded and the safety is engaged.
- Gather the necessary tools, including a screwdriver suitable for the screw heads.

2. Installation Steps

- Remove the existing screws from the trigger assembly using the appropriate screwdriver.
- Inspect the trigger and surrounding components for any signs of wear or damage.
- Take the new replacement screws from the package.
- Align the replacement screws with the holes in the trigger assembly.
- Insert the screws and handtighten them to avoid crossthreading.
- Once handtightened, use the screwdriver to secure the screws firmly, but do not overtighten.

3. PostInstallation Check

- After installation, check the trigger function to ensure it operates smoothly.
- Test the firearm in a safe environment to confirm proper operation before regular use.

Disposal Instructions

- Dispose of any old screws and packaging materials in accordance with local regulations.
- Do not dispose of screws in a manner that may pose a hazard to the environment or public safety.

Contact Information for Further Support

For any inquiries regarding safety, installation, or product performance, please contact the manufacturer directly. Ensure to have your product details handy for a more efficient response.

Thank you for your attention to these safety instructions. Your safety and the safety of others are our top priority. Always handle firearms responsibly and in accordance with local laws and regulations.